

SEKUR FT

PHOTOCELLS



FT33



FT23



FT43



FT42B

		FT33	FT23	FT43	FT42B
ELECTRICAL DATA					
power	Vac	12-24	12-24	12-24	12-24
	Vdc	12-35	12-35	12-35	12-35
range	m	25	25	25	20
consumption rx	mA	27	27	27	35
consumption tx	mA	10	10	10	0,04
relay contacts max supply	A	1	1	1	1
GENERIC DATA					
protection degree	IP	54	54	54	54
dimensions (L - D - H)	mm	80 - 33 - 90	30 - 28 - 90	35 - 35 - 110	35 - 35 - 110
operating temperature	°C	-20 + 55	-20 + 55	-20 + 55	-20 + 55

PLUS

New logic circuit with improved performance
Snow function: photocell activates an adaptatively temporized mode, in case of frequent dimming or

darkening, to avoid false obstacles detection
Two programmable rangesvw

MODELS

CODE	DESCRIPTION
FT33	Pair of photocells for external use and flush mounting
FT23	Pair of photocells for external use for small pillars
FT43	Pair of photocells for external use adjustable through 180°, for small pillars
FT42B	Pair of photocells for external use adjustable through 180°, for small pillars, battery powered

ACCESSORIES



BAT-3
Kit battery for FT42B



MUR-P
Plastic wall support for FT33

PC 1

PC 1